

Versi Pro 15 (GVP 15)

FEATURES

- 1 Patented pivot system provides a power curve to match each jaw set's primary application
- 2 360° rotation comes standard with every Versi Pro
- 3 Proprietary regeneration valve improves cycle time by up to 33% compared to standard hydraulic systems
- 4 Each jaw's pivot group stays intact, allowing the use of a press-fit pin design for a stronger, more durable product and making jaw change-outs safe, easy and fast
- 5 Jaw change-outs in 10 minutes with the coupler-style connection system



APPLICATIONS

Shear Jaws

- Scrap Processing
- Demolition
- Rebar
- Wire
- Tires
- Many types of non-ferrous

Cracker Jaws

- Demolition
- Concrete Recycling
- C&D Processing

Shear Jaws



Patented bolt-on piercing tip is replaced in minutes without grinding or welding

Four-way indexable guide blades, razor blade and primary blades provide four useable cutting edges

Exclusive dual guide blade system accommodates heat expansion at the tip while maintaining tighter tolerances where the primary cutting blades pass

Cracker Jaws



Offset teeth rows maximize the ability to downsize material

Patented pivot geometry creates peak power when jaws are near wide open, where it's most needed to crush concrete

Jaws	Weight*	Jaw Opening	Jaw Depth	Reach**	Minimum Excavator Weight	
	(lbs.)	(ins.)	(ins.)		Boom Mount (lbs.)	Stick Mount (lbs.)
Shear	3,200	16	15	7' 5"	18,000	28,000
Cracker	3,200	25	25	8' 3"	18,000	28,000

*Weight includes mounting bracket to attach to excavator.

**Distance is measured from the attachment mounting pivot (boom or stick) forward.

The GVP 15 body and jaws are available in black only.

The stability of each lift class varies between OEM excavator models. Please consult with your Genesis salesperson for recommended carrier models.

Every Genesis Versi Pro 15 is covered by a 12-month, 1,500-hour (whichever occurs first) warranty.

Patents: genesisattachments.com/products/patents